



# LPS 2<sup>®</sup> HEAVY-DUTY LUBRICANT



## FEATURES

- Strong, multi-purpose lubricant, and penetrant
- Provides a non-drying, light, oily film for use on indoor/outdoor equipment
- Reduces wear caused by friction and corrosion
- Loosens rusted or frozen parts
- Provides up to one year of corrosion protection on steel parts
- Nonfood Compounds Program Listed  
Category Code: H2 Registration  
#129026 (aerosol); #059848 (bulk)



## APPLICATIONS

- Bearings & Valves
- Cables & Linkages
- Dies, Bits & Fasteners
- Engines & Electric Motors
- Metal Parts
- Parts in Storage
- Production Equipment
- Pulleys & Rollers

### iS (IDENTIFICATION SYSTEM)



## AVAILABLE PRODUCTS

Part No.		Net Contents	Container	Case Pack	Case Wt.
US	Canada				
00216	C30216	11 wt. oz. (312 g)	Aerosol	12	12 lbs.
00222	C00222	20 fl. oz. (591 mL)	Trigger	12	16 lbs.
02128	C02128	1 gal. (3.78 L)	Container	4	33 lbs.
00205	C00205	5 gal. (18.93 L)	Pail	1	39 lbs.
00255	C00255	55 gal. (208 L)	Drum	1	418 lbs.



# LPS 2<sup>®</sup> HEAVY-DUTY LUBRICANT

## PROPERTIES

<b>Appearance/ Physical State</b>	Liquid	<b>Color</b>	Brown
<b>Odor</b>	Slight petroleum odor, Cherry	<b>Flash Point</b>	174.2°F(79.0°C) TCC
<b>Melting Point/ Freezing Point</b>	<-58°F (<-50°C)	<b>Percent Volatile</b>	92 - 95%
<b>Boiling Point/Range</b>	383°F (195°C) @ 101 kPa	<b>Dielectric strength</b>	33 kV
<b>Vapor Pressure</b>	<0.05 mm Hg @20°C	<b>Auto-ignition Temperature</b>	>442.4°F (>228°C)
<b>Flammability/ Explosive Limits</b>	Lower 0.6% Upper 7.0%	<b>Viscosity</b>	<7 cSt @ 77°F (25°C)
<b>Dielectric Strength</b>	33 kV	<b>VOC</b>	Aerosol: 0% per U.S. State and Federal Consumer Product Regulations  Bulk: 0% per U.S. State and Federal Consumer Product Regulations

## HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not re-use empty containers. Do not breathe gas. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Avoid contact with clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling.

## STORAGE

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°F/122°F. Do not puncture, incinerate or crush. Contents under pressure. Keep away from heat, sparks and open flame. Keep container tightly closed. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## DISPOSAL INFORMATION

Waste must be disposed of in accordance with any and all applicable environmental control rules and/or regulations.



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.lpslabs.com](http://www.lpslabs.com)

©2017 ITW Pro Brands • LPS<sup>®</sup> and LPS 2<sup>®</sup> are registered trademarks of Illinois Tool Works All Rights Reserved • TDS00216 • 170505