



THERMAPLEX® MULTI-PURPOSE

BEARING GREASE



FEATURES

- Ideal for lubricating all types of bearings
- Extends relubrication periods
- Prolongs bearing life
- Excellent load carrying properties
- Good corrosion resistance
- Reduces grease consumption
- “Product of the Year” winner for Lubricants World Magazine



PACKAGES

Net Fill	Part No.
14.1 oz. (400 grams) cartridge	70614
35 lbs. (5 gallons) pail	70606
120 lbs. (16 gallons) keg	70635
400 lbs. (55 gallons) drum	70655

APPLICATIONS

- Cement Mixers
- Elevators
- Motors
- Ventilator Fans
- Conveyors
- Gas Extractors
- Tray Loaders

PROPERTIES

4-Ball Weld Load:
>600 kg

Appearance/Physical State:
Creamy Paste

Base Oil Viscosity:
850 SUS @ 100°F
180 cst. @ 40°C
17 cst. @ 100°C

Color:
Blue

Copper Corrosion
1A/1B

Dropping Point:
429°F (220°C)

Flash Point:
>392°F (~200°C) PMCC

NLGI Grade:
2

Odor:
Petroleum

Specific Gravity (water=1):
1.00

Temperature Range:
-22°F (-30°C) to 350°F (177°C)

Thickener Type:
Lithium Complex

Timkin “OK” Load:
50 lbs.

Vapor Density (air=1):
>1

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE: WWW.LPSLABS.COM

LPS Laboratories • An Illinois Tool Works Company

4647 Hugh Howell Road • Tucker, GA 30084 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2012 LPS Laboratories • LPS® and ThermoPlex® are registered trademarks of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2155 • Rev. 6/2012