

### Description

835-P *Rosin Flux Pen* contains a type R rosin-activated flux, composed of pure white-water gum rosin, a unique solvent system, and very effective activators. The superior fluxing remains consistent throughout the entire aeration process. 835-P provides fast wetting action. 835-P complies with all requirements for type ROM1 flux per J-STD-004. A chiseled tip provides exact delivery of flux to surface.

### Application

835-P Rosin Flux Pen is designed to dispense flux in a precise application. Excellent for prototyping and rework/repair on printed circuit boards. Works well on chip carriers, heat sinks, surface mounted device pads, switches and sockets.

### Features & Benefits

- **Fast wetting**
- **Non-corrosive**
- **Non-hygroscopic**
- **Halide free**
- **RoHS compliant**
- **Controlled application**

### Flux Paste Properties

<i>Flux Properties</i>	<i>Method</i>	<i>Value</i>
Flux type Flux Activity Halides %(wt) Flux Classification	J-STD-004 MIL-F-14256F	Rosin Moderate 0.44% ROM1 RA
<i>Physical Properties</i>	<i>Method</i>	<i>Value</i>
Color Solids% Density Flash Point	Closed cup	Light amber 50% 0.93 12 °C [53 °F]

### Storage and Shelf Life

Store at around room temperature and protect from direct heat or sunlight.

<i>Properties</i>	<i>Value</i>
Shelf Life after DOM	2 years
Storage Temperature	18 to 27 °C [65 to 80 °F]

DOM = date of manufacture

## Cleaning

If removal is desired, a solvent system like the *MG 4140* or *MG 413B* can be used. For best results, warm the cleaning solution to about 40 °C [104 °F].

## Health and Safety

Please see the 835 **Safety Data Sheet** (SDS) for more details on transportation, storage, handling and other security guidelines.

**Environmental Impact:** The volatile organic content is 50% by EPA and WHMIS standards.




This product meets the European Directive 2011/65/EU Annex II (ROHS); recasting 2002/95/EC.

**Health and Safety:** Avoid breathing fumes. Wash hands thoroughly after use. Do not ingest.

### HMIS® RATING

### NFPA® 704 CODES

<b>HEALTH:</b>	* 2
<b>FLAMMABILITY:</b>	3
<b>PHYSICAL HAZARD:</b>	0
<b>PERSONAL PROTECTION:</b>	



*Approximate HMIS and NFPA Risk Ratings Legend:*

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

## Application Instructions

Apply flux by direct dispensing via the pen.

## Packaging and Supporting Products

### Product Availability

<i>Cat. No.</i>	<i>Form</i>	<i>Net Volume</i>	<i>Net Weight</i>
<b>835-P</b>	Pen	10 mL 0.34 fl oz	9.3 g 0.33 oz

### Suitable Flux Cleaners

- *Heavy Duty Flux Remover:* Cat. No. 413B-1L, 413B-4L, 413B-20L, 413B-425G
- *Flux Remover for PC Boards:* Cat. No. 4140-P, 4140-400G, 4140-1L, 4140-4L, 4140-20L

## Technical Support

Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at [www.mgchemicals.com](http://www.mgchemicals.com).

Email: [support@mgchemicals.com](mailto:support@mgchemicals.com)

Phone: 1-800-340-0772 (Canada, Mexico & USA)  
1-905-331-1396 (International)

Fax: 1-905-331-2862 or 1-800-340-0773

Mailing address: **Manufacturing & Support**  
1210 Corporate Drive  
Burlington, Ontario, Canada  
L7L 5R6

**Head Office**  
9347-193rd Street  
Surrey, British Columbia, Canada  
V4N 4E7

## Warranty

*M.G. Chemicals Ltd.* warrants this product for 12 months from the date of purchase by the end user. *M.G. Chemicals Ltd.* makes no claims as to shelf life of this product for the warranty. The liability of *M.G. Chemicals Ltd.* whether based on its warranty, contracts, or otherwise shall in no case include incidental or consequential damage.

## Disclaimer

This information is believed to be accurate. It is intended for professional end users having the skills to evaluate and use the data properly. *M.G. Chemicals Ltd.* does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.