



D3051 - Double sided tissue tape

Description	Double coated tissue tape with a solvent acrylic adhesive.
Product properties	It provides good holding power and has a good performance at elevated temperatures
Applications	plastic bag sealing, Paper splicing, Name plate bonding, Seamless catrboard bonding
Storage and ageing	1 year shelf life whilst stored in original packaging and ambient room temperature. Keep out of direct sunlight.
Applying tips	All substrates should be clean and contamination free, a solvent such as Isopropyl-Alcohol is recommended for cleaning purposes, and the tape should be applied with pressure.
Additional technical properties	Rolling ball test 120mm Static shear test at 23C - 800 minutes according GB/T2792-1998 Static shear test at 80C - 15 minutes according GB/T4851-1998

TECHNICAL DATA

Carrier	Tissue	
Adhesive	Acrylic	
Colour	Translucent	
Liner	Paper silicone coated white	
Thickness Total	0,11 mm	4,33 Mils
Adhesion on stainless steel	14 N/25mm	3,2 Lbs/inch
Service temperature	Between -30 and 120 °C	Between -22 and 248 °F
Application temperature	Between 8 and 38 °C	Between 46,4 and 100 °F

Disclaimer: Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available "as is" and that Stokvis Tapes, an ITW company, gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information.

See our applicable delivery conditions. Each user should conduct his own tests to determine the suitability of the product for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes cannot be held liable for any damages resulting from the unsuitability of the product. Many factors beyond the control of Stokvis Tapes may affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

The information is available to the user for viewing, copying and distributing, provided that Stokvis Tapes, an ITW company, is always quoted as the source. The information is intended solely for informational and non-commercial use.

Intellectual property: Stokvis Tapes, an ITW company, reserves all rights regarding this document and the information contained herein. Reproduction, use or disclosure to third parties without express permission is strictly forbidden.

Stokvis Tapes (UK) Ltd
Unit 8, Tring Industrial Estate
Icknield Way, Tring, Hertfordshire
tel +44 (0)14 42 82 17 00
fax +44 (0)14 42 82 17 22
www.stokvistapes.co.uk
info@stokvistapes.co.uk