



## DSPR397 - Double Sided PET Tape

<b>Description</b>	This double sided tape consists of a polyester carrier and a solvent based modified acrylic adhesive.
<b>Product properties</b>	It has a very good resistance against UV light, temperatures, chemicals, solvents and humidity. Its high shear resistant adhesive is highly durable on metal, varnish and high-energy surfaces. It has a good adhesive durability when attached to low-energy surfaces, and because of its high adhesive mass, it is appropriate for rough or structured surfaces.
<b>Specifications</b>	EU directive 2002/95/EC (RoHS) Is lmds registered Is Rohs compliant
<b>Applications</b>	It is used for the secure attachment of truck and car mirrors in plastic housings and as an adhesive medium for trims, covers and cable trunks. It is used for the extension and splicing of paper, textiles, plastic and metal films, where high shear strength and adhesion is required.
<b>Storage and ageing</b>	2 year shelf life whilst stored in original packaging and ambient room temperature. Keep out of direct sunlight.
<b>Applying tips</b>	All substrates should be clean and contamination free, a solvent such as Isopropyl-Alcohol is recommended for cleaning purposes, and the tape should be applied with pressure.

**Stokvis Tapes (UK) Ltd**  
Unit 8, Tring Industrial Estate  
Icknield Way, Tring, Hertfordshire  
tel +44 (0)14 42 82 17 00  
fax +44 (0)14 42 82 17 22  
www.stokvistapes.co.uk  
info@stokvistapes.co.uk

An Illinois Tool Works Company 

