

ELECTRICAL DEGREASER



EL™ 749



For use on Electrical Equipment (VOC 75)

NSF

K2

NSF® Registered; K2 Rated (Solvents for cleaning electronic instruments) (Registration # 115068)

VERY
FAST
EVAP

Evaporation Rate: Very Fast



Flammable



Do not use on plastics

KB

85

KB Solvency Strength (higher value, stronger the solvent): 85



HMIS Hazard Rating:
Health (2) • Flammability (4) • Reactivity (0)

- Alternative to 1,1,1 Trichloroethene
- For use on non-energized equipment
- Leaves no residue
- Dielectric strength 16,800 volts



PRESERVE. PROTECT. PREVENT.™

Sprayon® EL™ 749 Electrical Degreaser is a heavy duty cleaner which penetrates quickly to remove dirt, oil, grease, wax, and tar. Leaves no residue. Contains no Class I or Class II compounds. Dielectric strength of 16,800 volts. Aerosol is equipped with high delivery valve for cleaning efficiency and an extension tube for hard to reach areas.

ELECTRICAL & ELECTRONIC

USES

- Relays • Air tools
- Wire rope • Gears
- Molds • Sprockets
- Clutches • Brakes
- Dies • Locks
- Generators • Chains
- Radar Equipment
- Air conditioners
- Electrical motors
- Material handling equipment

APPLICATION

For food plant and other industrial use only. Avoid contamination of food during the use and storage of this product. Spray in well ventilated area. Sprays best at room temperature (70°F). Shake well before using. NOTE: Do not use on electrical equipment while in operation. Allow surface to dry completely before restart. May harm certain plastics, elastomers and air-dry painted surfaces. Test product on non-essential similar material prior to application.

PERFORMANCE

- EVAPORATION RATE: Fast
KB VALUE (Cleaning Power): 85
DIELECTRIC STRENGTH: 16,800 volts
PLASTIC SAFE: No
- NSF Registration Number 115068; K2 Rated
 - Alternative to 1,1,1 Trichloroethene
 - For use on non energized equipment
 - Leaves no residue
 - Meets California's Consumer Regulation (CONS-1) for Electrical Cleaner
 - Equipped with an extension tube for hard-to-reach areas

PROPERTIES

- APPEARANCE: Clear Volatile Liquid
ODOR: Sweet/Strong
PROPELLANT: CO₂
WT./GAL.: 6.08
SPECIFIC GRAVITY: 0.73
% VOC AEROSOL: 45%
V.O.C. COMPLIANT CALIFORNIA: Yes
V.O.C. COMPLIANT OTC STATES: Yes
FLAMMABLE: Yes
FLASH POINT: 3°F
HAZARD RATING: 2,4,0
SHELF LIFE: 3 years from date of manufacture

PACKAGING

- Stock #: S00749
UPC Code: 0-75577-90749-6
Fill Wt: 15 oz.
Per Case: 12
Carton Dimensions:
L 10-7/8" x W 8-3/16" x H 9-5/8"

RESOURCES

- MSDS/EDS/PRODUCT DATA
SHEETS: sprayon.com
CUSTOMER SERVICE: 1-800-777-2966
TECHNICAL INFORMATION: 1-800-251-2486



SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.



EL749



© 2010 Sprayon® Products Made in U.S.A.

Distributed by:

PRESERVE. PROTECT. PREVENT.



Sprayon® Products
101 Prospect Ave. NW
Cleveland, OH 44115
Sprayon.com
1-800-777-2966

www.technical.co.uk

310-PDS-EL749